



INSTRUCTIONS



MODEL : HONDA CB 500X 13+

PRODUCT : FENDER EXTENDER

CODE : FE-HCB500X13

CONTENTS

Plastic Mud Guard
3M VHB Tape

MATERIAL SPECIFICATIONS

The product's material, made of **ABS** plastic with acrylic exterior layer, can be placed on your bike without requiring painting but if you want it painted, all paint companies have equivalent machinery at their disposal. If you want to paint it yourself, you should contact them to inform you on what you will need and how to do it.



Photo No 1



Photo No 2

Placement

OUR COMPANY SUGGESTS THE INSTALLATION BE CARRIED OUT AT A WORKSHOP OR BY QUALIFIED STAFF

- Remove the front fender – clean it carefully with soap-water and then dry it.
- Place the fender extender on the wing to see its exact placement and mark it on the outer side with a marker tape (Photo No 1)
- Clean with some alcohol the fender's inner side.
- Remove the protective film from the 3M VHB tape (mud guard tape) and it stick it on the spot you have marked.
- Push firmly the two pieces in place along the whole surface (Photo No 2).
- Reposition the front fender.

IMPORTANT NOTICE: for 5 hours do not wash your motorcycle and keep the wing clear of water and mud. Optionally, you may also add small drops of silicone glue between the tapes, but keep the silicone away from the tapes' edges.

