

INSTRUCTION

Model	Product	Code
Yamaha XSR 700 2016+	Leatherette Seat Cover	LSC-XSR-DBR-BL

You are advised to read the instructions carefully, before you proceed to any changes. Any modifications on your motorcycle should be performed by specialized personnel, however the installation process of this product is quite easy if you follow the instructions below.



CONTENTS

Leatherette Cover

You can see in the photo all the required tools to perform this task.



1

2

Undo all the old screws that hold the cover in place.



Make sure the foam is dry and clean.









Pull tight along the perimeter of the seat so that the rubber is underneath the seat

Start nailing the leatherette cover first on the right and then on the left hand side and approximately along the middle of the seat. Make sure you nail it underneath the rubber and not on it. Pull tightly to make sure the cover has tightened properly.

Use a nail at the rear centre part of the cover – make sure it is placed precisely in the middle.

Place a nail at the front end of the seat , one one the right side and one on the left side – before you do that make sure you've spread the leatherette evenly and rightly centered. Then start nailing the cover in place,

going along its perimeter (every 2-3 cm), by pulling it tightly and always underneath the rubber.

At the front end where there is no piece of rubber, nail it in a circular motion, approximately 2 cm off the outer part.



2/3



5

3

Finally, you may place 3-4 nails on the leatherette so that it doesn't stick out.

At the front end cut in a circular motion.

You can see the end result in the photo. Thank you for choosing one of our products. You may watch the installation video at the following link: https://youtu.be/5mi20yAVe0A

For any further information please do not hesitate to contact us: Tel.: +30 2108075387 Email: info@c-racer.com



Once you have finished, start cutting off the remaining leatherette beneath the rubber.

The product is for race use only









10

8