

INSTRUCTION

Model	Product	Code
Yamaha XSR 700 2016+	Mask for Flat Track	MCRFT-YXSR

You are advised to read the instructions carefully, before you proceed to any changes.

Any modifications on your motorcycle should be performed by specialized personnel, however the installation process of this product is quite easy if you follow the instructions below.



CONTENTS

- 1 X plastic mask
- 1 X clip M6 (sliding)
- 5 X screws M6X15 (allen-roundhead-washer)
- 5 X washers M6X18 (plastic)



Undo the cover in front of the main switch and slide through the main hole the M6 clip that is included in the package.



Undo the side screws and remove the flash light – be careful as you undo the screws for it might fall off.

Make sure you're holding it with your hands until it's placed on the fender.

You don't have to remove all three screws of the side plate –if you remove just the two rear screws you can pull it out sideways.



3

4





The main connector is seated on a clip. Use a small screwdriver to release it and pull it outwards. You need to push it as is shown in the above photo and then pull it out completely. (you need to release the attachments on all three sides of it.



Then you may put the mask in place and screw it tight.



The end result should appear as in the photo on the left.

Thank you for choosing one of our products.

You may watch the installation video at the

You may watch the installation video at the following link: https://youtu.be/HG2f4QDBnXA



For any further information please do not hesitate to contact us: Tel.: +30 2108075387 Email: info@c-racer.com