

INSTRUCTION

Model	Product	Code
Yamaha XSR 700 2016+	Headlight Mask for Flat Track	MCRFTL-YXSR

You are advised to read the instructions carefully, before you proceed to any changes.

Any modifications on your motorcycle should be performed by specialized personnel, however the installation process of this product is quite easy if you follow the instructions below.



CONTENTS

- 1 X plastic mask
- 4 X metal bracket
- 1 X headlight with extension cord
- 2 X screws M5X20
- 2 X clips M5 (sliding)
- 1 X clip M6 (sliding)
- 5 X screws M6X15 (allen round head washer)
- 5 X washers M6X18 (plastic)



Place the wire behind the headlight.



Undo the cover infront of the main switch and place the M6 clip on the centre hole.



Undo the side screws and remove the headlight – be careful not to drop the headlight once you undo the screws.

Make sure you're holding it until it falls on the fender.

You don't have to remove all three screws of the side headlight brackets – if you remove only the two rear ones you can pull it out.

1 & 2





The main connector is supported by a clip. Use a small screwdriver to unfasten it so that it protrudes. You have to push it out as shown in the photo above and then disconnect it completely – release the attachments on all three sides.





Connect the headlight with its wire to the main connector – you will use the two centre pairs of the connector.

Now check to see if you can turn on the headlight by pressing the switch.

Then you may proceed with putting the mask in its position and fastening it using the screws.



If you want, you can also put your liking on the flash you'll need.

The end result should appear as in the photo on the left.

Thank you for choosing one of our products. You may watch the installation video at the following link: https://youtu.be/WALQewh5Q70